

A2Z Series Models: 3035, 3036, 3096**Specifications:**

- 5 leg base: Molded engineered black resin with metal insert, textured finish, 23" span.
- Casters: 2" (55mm) hard tread hooded dual wheel casters.
- Seat: Molded hardwood structural upholstery grade plywood seat board fitted with metal threaded inserts; dual density poly urethane foam padding.
- Backrest: Molded engineered resin rigid form with mating resin back. Resilient dual density polyurethane foam padding.
- Back Support: Steel bar in black finish. ¼" x 2 ¼" standard.
- Control Mechanisms:
 - The standard control mechanism on all models provides swivel-only action combined with a horizontally adjusting "J-Bar" enabling user-friendly seat depth adjustment via a convenient hand-wheel. The backrest pivots freely at the upper end of the back support to follow the users' back support angle need.
 - The optional control mechanism is a swivel-tilt control mechanism combined with a gravity backrest height adjustment (SWT-BHA). Included are tilt tension and adjustment hand-wheel and upright position tilt-lock lever. The backrest supporting "J-Bar" is attached to the seat board with steel fasteners into threaded metal inserts. The swivel-tilt control option is not available on stool model.

Seat Height Adjustment:

All models are equipped with pneumatic cylinders operated with a user-friendly lever incorporated in the control mechanism. Task models feature 5 inches seat height range (140 mm stroke); stool models feature 8 inches seat height range (200 mm stroke).

Armrests:

Horizontally and vertically adjustable "T" arms are standard on models 3036 and 3096. Supports for armrests are formed steel bars. Armrest pads are self-skinned molded polyurethane foam with steel inserts. A spring-biased button provides easy height adjustment in small fixed increments: horizontal adjustment in small infinite increments is enabled by a hand-wheel release on each arm.

Upholstery:

Available in a complete range of Lux Steel, Inc. textiles or COM (Customer Owned Material). Upholstery technique features side facing on seat and backrest featuring French seaming (Double Needle) for added durability and aesthetics.

60-8 Polyurethane Stool

Specifications:

- Rugged Self-Skinned polyurethane back and seat are resistant to grease, water, chemicals and other spills.
- Easy wipe down to keep clean.
- Features 360 degrees swivel mechanism with pneumatic height. adjustment (8" overall adjustment in height)
- Five legged nylon base with metal reinforced hub.
- Seat and back have ventilation ribs molded into their structure.
- Standard with hard wheel casters.
- Seat height from floor range (20.5" – 28.5")
- 18" chrome footring standard.
- Footring has 7" height adjustment.
- Seat is 18" wide and 17" deep with a waterfall front edge.
- Overall back height range is from 35.5" – 43.5".